



QIROX QRC-410

6-axis robot mechanics with classic wrist and 4,100 mm working envelope

The QIROX QRC-410 is a six-axis articulated arm robot. The robot is used in upright or overhead position and is mounted on a base or directly at a robot positioner. The QIROX QRC-410 has a classic wrist where welding torches, flame cutters and other working tools with a weight of up to 10 kg can be mounted. The integration of a changing tool on the wrist allows the application of more processes with a robot.

- All-rounder: Carries out many different task due to the use of a changing tool and a maximum payload of 10 kg at the wrist
- Processes: Takes over all MIG/MAG and TIG welding processes, optionally leads a laser sensor and carries out cutting tasks
- Flexibility: Modular design for tailor-made systems, perfectly adapted to individual production requirements
- Dynamics: High dynamics due to slim product design, low weight and ergonomic shapes
- Quality: Repeatability, long service life and maintenance intervals





QIROX QRC-410

Technical Data

Series	WL
Design	Classic
Number of axes	6
Payload	10 kg
Working area	4100 mm
Mounting area	500x510
Robot weight	225 kg
Mounting	Boden Decke
Processes	Plasma and oxy-fuel cutting MIG/MAG welding MIG/MAG welding (WDD) MIG/MAG Tandem welding MIG/MAG Tandem welding (WDD) TIG welding TIG Welding (WDF) Laser cutting Laser welding Handling
Attachment parts	Greifer Offline Lasersensor Online Lasersensor Taktile Taststift Wechselsystem

Process

- Plasma and oxy-fuel cutting
- MIG/MAG welding
- MIG/MAG welding (WDD)
- MIG/MAG Tandem welding
- MIG/MAG Tandem welding (WDD)
- TIG welding
- TIG Welding (WDF)
- Laser cutting
- Laser welding
- Handling

Questions about the product?

Your contact partner
Manuel Benner
Tel.: +49 (0)2773/85-562
Automation@cloos.de



Technical modifications reserved
Version: 20.05.2024

CLOOS