QINEO WDB-20

Additional wire drive unit for a safe wire feed over long distances

The additional wire drive unit feeds the wire over a maximum distance of approx. 30 meters from a wire drum to the main wire drive. The feeding of the additional wire drive unit depends on the feeding speed of the main wire drive unit. The transport takes place with little wear and almost no friction through a wire spiral with a large diameter.

- Wire feed over long distances enables the wire drum to be positioned in an easily accessible place
- Safe wire feed over a distance of up to 30 meters between wire drum and main wire drive unit







QINEO WDB-20

Wire feed speed max. 30 m/min	Technical Data	
	Wire feed speed	max. 30 m/min
Dimensions L/W/H 300/260/180 mm	Dimensions L/W/H	300/260/180 mm
Weight 6,2 kg	Weight	6,2 kg
Wire diameter 0.8 - 2.0 mm	Wire diameter	0.8 - 2.0 mm

Application

Auto

Process

- MIG/MAG Single Wire
- MIG/MAG Single Wire pulse
- MIG/MAG Single Wire AC
- MIG Bracing
- MIG/MAG Tandem

Questions about the product?

Your contact partner: Daniel Weber Tel.: +49 (0)2773 85-430 gt-sales@cloos.de mage not forund or type

Technical modifications reserved Version: 29.04.2024

