



QIROX QRC-230

6-axis robot mechanics with classic wrist and 2,300 mm working envelope

The QIROX QRC-230 is a six-axis articulated arm robot. The robot is used in upright or overhead position and is mounted on a base or directly at a robot positioner. The QIROX QRC-230 robot has a classic wrist where welding torches and other working tools with a weight of up to 12 kg can be mounted.

- Compact solution: Agile and highly dynamic for short cycle times
- Processes: Takes over all MIG/MAG and TIG welding processes, optionally leads a laser sensor
- Flexibility: Modular design for tailor-made systems, perfectly adapted to individual production requirements
- Dynamics: High dynamics due to slim product design, low weight and ergonomic shapes
- Quality: Repeatability, long service life and maintenance intervals





QIROX QRC-230

Technical Data	
Series	WM
Design	Classic
Number of axes	6
Payload	12 kg
Working area	2300 mm
Mounting area	400x400
Robot weight	107 kg
Mounting	Inclination Boden Wand Decke
Processes	TIG Welding (WDF) MIG/MAG Tandem welding MIG/MAG welding (WDD) TIG welding MIG/MAG Tandem welding (WDD) Handling MIG/MAG welding
Attachment parts	Greifer Offline Lasersensor Online Lasersensor Taktiles Taststift Wechselsystem

Process
<ul style="list-style-type: none">• TIG Welding (WDF)• MIG/MAG Tandem welding• MIG/MAG welding (WDD)• TIG welding• MIG/MAG Tandem welding (WDD)• Handling• MIG/MAG welding

Questions about the product?

Your contact partner
Manuel Benner
Tel.: +49 (0)2773/85-562
Automation@cloos.de



Technical modifications reserved
Version: 20.05.2024

CLOOS