




## QIROX QRH-360-H

**6-axis robot mechanics with hollow shaft wrist, 3,600 mm working envelope and a high base for floor mounting**

The QIROX QRH-360-H is a six-axis articulated arm robot. The robot is mounted in upright position on the floor or directly at a robot positioner. The QIROX QRH-360-H has a hollow shaft wrist in which the welding technology is integrated.

- Flexibility: Modular design for tailor-made systems, perfectly adapted to individual production requirements
- Processes: Takes over all MIG/MAG single wire welding processes
- Welding specialist: The hollow shaft integrated in the wrist ensures an optimum wire guide of soft and thin welding wires and an increased level of stability of the torch cable assembly.
- Dynamics: High dynamics due to slim product design, low weight and ergonomic shapes
- Quality: Repeatability, long service life and maintenance intervals





## QIROX QRH-360-H

### Technical Data

|                |                                          |
|----------------|------------------------------------------|
| Series         | WL                                       |
| Design         | Hollow wrist                             |
| Number of axes | 6                                        |
| Payload        | 15 kg                                    |
| Working area   | 3600 mm                                  |
| Mounting area  | 500x510                                  |
| Robot weight   | 220 kg                                   |
| Mounting       | Boden                                    |
| Processes      | MIG/MAG welding<br>MIG/MAG welding (WDD) |

### Process

- MIG/MAG welding
- MIG/MAG welding (WDD)

### Questions about the product?

Your contact partner  
Manuel Benner  
Tel.: +49 (0)2773/85-562  
Automation@cloos.de



Technical modifications reserved  
Version: 20.05.2024

CLOOS